



Dickinson Cameron Construction Company, Inc.

CODE OF SAFE CONDUCT

- BE ALERT! Report unsafe conditions immediately. All incidents, no matter how minor, are to be reported immediately to the DCC Project Superintendent.
- All visitors must check in with the Project Superintendent prior to going on site.
- Any person on site, including workers, supervisors, clients, visitors, and vendors, must wear hardhats at all times.
- All workers must wear clothes suited to the job. No dangling or loose clothing or jewelry around moving machinery. Shirts with minimum 4" long sleeves, work boots, and long pants are required.
- No radios, CD players, DVD Players, MP-3s, boom boxes, players, or any other form of entertainment media that provides amplified sound, whether free standing or headset will be allowed on site.
- Reporting for work under the influence of intoxicants or narcotics or consumption of them during the workday will result in removal from the jobsite
- Smoking on the project is forbidden except in specific locations designated by Project Superintendent.
- Horseplay, fistfights, whistling, yelling at the public or obscene gestures will result in removal from the jobsite.
- Eye protection will be required as prescribed by Cal/OSHA standards and manufacturer recommendations.
- Hearing protection, earmuffs or approved earplugs, will be worn on all high noise level tasks as required by Cal/OSHA.
- Subcontractors are required to maintain Class B first aid equipment and supplies in their work areas.
- All Subcontractors are responsible for daily housekeeping in and around their work areas and to place their trash into the designated trash receptacle before the end of each work day.
- Attendance at weekly safety meetings and documentation of meetings is mandatory.
- A job hazard analysis will be completed for all high hazard or non-routine jobs.
- Any product brought on site must have a Safety Data Sheets (SDS) on file with Project Superintendent.
- Tampering with or unauthorized use or removal of fire extinguishers from locations is prohibited.
- No one will operate any trucks, loaders, backhoes, or other equipment unless specifically certified to do so.
- Before digging in any location, check to ensure that all underground utilities have been located and properly marked.
- Excavations over 4 feet must be sloped, shored, or shielded, and must follow CCR, Title 8, 1539-1547.
- Barricades are required around excavations, holes, or openings in floors or roofs, edges of roofs, and whenever necessary to warn or prevent people or equipment from failing.
- Guardrails or fall protection must be provided for all work areas where there is a potential for fall of 6 feet or more.
- Materials, tools, or other objects shall not be thrown from buildings or structures.
- No one shall enter manholes, underground vaults, chambers, tanks, or silos or other similar places that receive little ventilation, unless it has been determined that it is safe to enter.
- All work using cords or power tools must utilize Ground Fault Circuit Interrupters (GFCI) protection.
- When working on energized systems or equipment Cal/OSHA's lockout/tagout rules and regulations must be followed.
- Power tools shall be operated only by authorized personnel with guards 'in place'. Damaged tools shall be tagged 'DO NOT USE' and removed from service immediately.
- Powder-actuated tools require certified training before use.
- DCC supervisory personnel have the authority to remove any unsafe tools, equipment, and workers from the jobsite.
- When lifting heavy objects use the large muscles of the leg instead of the muscles of the back.
- **ALL SUBCONTRACTORS must provide proof of current liability and workers comp insurance UPON ARRIVAL to jobsite and prior to starting work.**